

Variable message sign available

with or without radar detector.

Ideal to warn, inform or guide road users.

Time scheduled programming.

Up to 8 images can be displayed at different setting speeds.

Speed values displayable from 5 to 255 km/h.

| Altezza carattere max. Risoluzione 32 x 28 (896 LED) Photovoltaic kit + 2 Basic 201: - 90 Ah Power supply kit 230 VAC/12 V 12VDC Power supply/Battery kit 230 VAC/12 V 18 Ah Batter Software Included / App Android Connection Bluetooth (100m outdoor) e-mail GSM-GPRS-GI RS232 Vehicle detection Bidirectional (only statistic) | ED colour | | |
|--|------------------|--------------------------------|----------------------|
| Powered by Power supply kit Power supply/Battery kit Power supply/Battery kit Power supply/Battery kit Power supply/Battery kit 1230 VAC/12 V 18 Ah Batter Software Included / App Android Connection Bluetooth (100m Optional: e-mail GSM-GPRS-GI | | cm | |
| Powered by Power supply kit 230 VAC/12 V Power supply/Battery kit Power supply/Battery kit 230 VAC/12 V 18 Ah Batter Software Included / App Android Connection Bluetooth (100m Optional: e-mail GSM-GPRS-GI | isoluzione | x 28 (896 LED) | |
| Powered by Power supply/Battery kit Power supply/Battery kit 230 VAC/12 V 18 Ah Batter Software Included / App Android Connection Bluetooth (100m outdoor) e-mail outdoor) e-mail GSM-GPRS-GI | Powered by | + 2 B | asic201: 100W |
| Software Included / App Android Connection Bluetooth (100m outdoor) e-mail GSM-GPRS-GI | | 230VAC H 230 \ | /AC/12 VDC |
| Connection Bluetooth (100m outdooor) e-mail GSM-GPRS-GI | | 230 \ | |
| Connection outdooor) e-mail RS232 GSM-GPRS-GI | oftware | Included / App Android | |
| Vehicle detection Bidirectional (only statistic) | onnection | tdooor) e-ma | il |
| | ehicle detection | Bidirectional (only statistic) | |
| Dimensions 685 x 720 x 60 mm | imensions | 685 x 720 x 60 mm | |



Some examples of views:





















